

EC Dot Matrix Printer



EC-PM-530D

Features

- ESC/POS & START command sets compatible
- Interface: Ethernet+USB / Parallel / Serial+USB / Bluetooth / WiFi
- Standard simplified / traditional Chinese characters library
- Built-in large data buffer
- Windows driver, Linux driver, OPOS driver available



Specifications

Print method	9-pin impact dot matrix
Print Resolution	160 x 144 dpi (Max)
Max Printing Width	Max.63.4 mm
Paper Thickness Support	- Single sheet roll paper: 0.06 - 0.085 mm - Two-sheet, trilog copy paper (each page): 0.05 ~ 0.08 mm - total thickness ≤ 0.20 mm
Print speed	Max.4.7 LPS (40 columns,16 cpi)
Interface	Ethernet+USB / Parallel / Serial+USB / Bluetooth / WiFi
Driver	Win 9X / Win ME / Win 2000 / Win 2003 / Wint NT/ Win XP/ Win Vista, compatible with EPSON Support
Kitchen Print	
Character Size	ASCII sets, International character sets; Big 5 15x16 character (for HK and Taiwan version)
Fonts	GB18030
Power supply	DC 24V/2.5A
Power Adaptor Input	AC100V ~ 240V, 50~60HZ
Power Adaptor Output	DC 24V/2.5A
Weight	2.9kg
Dimension	162 W x 253 D x 132 H (mm)
Work environment	Temperature:5~ 35°C, Humidity:25 ~ 80%
Reliability- Mechanism	150km

Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P.64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx