

All-in-one POS Terminal



EC-VP-3100A

Features

- 15.6" Bezel free with Capacitive touch
- Flexible architectures for peripheral
MSR / VFD / iButton / Finger Sensor
- 10.1" / 15" Second display supported
- Hidden cable management

Specifications

Processor
System Memory
Storage Device

OS Supported

Display Size
Touch
Resolution
Brightness
Contrast Ratio
Response Time
Viewing Angle
(Up/ Down/ Left/ Right)
Video Interface

I/O Interface

Power

Operating Temperature
Operating Humidity
Dimensions (W x D x H)
Packing Dimensions (W x D x H)

Safety
IP Rating
Optional Peripherals

RK3288/cortex A17 1.8G
2GB / 4GB
8/16/32GB SSD

Android 5.1/6.1/7.1 with Google Play

15.6 Inches
10-point Projected Capacitive Touch
1366 x 768 / 1920 x 1080
220cd/m²
600:1
12ms

IPS
EDP

DC12V IN / DC12V OUT
1 x HDMI
6 x USB2.0
1 x AUDIO
1 x LAN
3 x COM(DB9)
1 x CASH DRAWER(RJ11)
1 x SD Slot

Input: AC 100-240V
Output: DC 12V/5A
-10°C ~ 50°C (14°F ~ 122°F)
15% ~ 85%
387 x 200 x 315 mm, N.W. 4.9 Kg
440 x 310 x 413 mm, G.W. 6.8 Kg

FCC / CE / RoHS
IP54
ISO Trick 1/2/3 Magnetic Stripe Reader
VFD / Second Display (10.1", 15")
iButton / Finger Sensor



Asia, Pacific: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P. 64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx