DUAL-CORE FANLESS TOUCH TERMINAL

EC Terminal

Waterproof

Powered by ELO

EC-1550
Specifications

CPU Type	Intel® Atom TM dual core processor D525 1.80 GHz (1M L2 Cache)
LCD	15” Active TFT color LCD, resolution 1024x768
Touch	ELO 5-wire Resistive Touch
Memory	DDR3 SO-DIMM 1GB (2 x sockets support up to 4 GB)
LAN	10/100/1000 Mbps Gigabit Ethernet
Storage	Internal 2.5” SATA HDD x 1
I/O Interface	4* COM ports (COM1~2 powered with DC+0/5/12V via BIOS selection; COM3~4 without power)
	1 * DB-15 VGA port
	1 * DB-25 for LPT port
	1 * RJ11 port supports 2 cash drawer (DC+24v)
	1 * RJ-45 LAN port with activity and link LEDs
	1 * PS/2 KB
	1 * DC+12V out
	4 * USB 2.0
	1 * DC + 12V in (power adaptor)
Expansion Options	1 * Mini PCI-e
Optional Peripherals	3 Tracks Magnetic Reader
	Customer Display Module (2 x 20 VFD)
Operating System	Windows 7, Windows XP, XPe,Linux, (ubuntu , fedora), WEPOS, POSReady.
Adaptor	AC100~240V/DC+12V, 90 watts power adaptor
Dimensions	Physical:360 mm (W) x 233 mm (D) x 323 mm (H)
Operating Temp	0º C~+ 40º C
Storage temperature	-20º C~+ 60º C
Humidity	15%~80%
Certification	CE, FCC, CCC, VCCI, BSMI, Class A, KC

*specification subject to change without prior notice