

# All-in-one POS Terminal



## EC-1559

### Features

- CPU J1900
- 2GB Ram; 64GB SSD or 320GB HDD
- Bezel free panel
- Powered with Elo resistive touch screen
- Grade A industrial grade LCD monitor
- Wall mount Vesa mounting
- IP 65; waterproof / dust proof / oil proof
- Various interfaces combination



### Specifications

LCD  
Touch  
CPU  
Memory  
Storage  
Operation System

15" Active TFT color LCD, 350 nits resolution 1024 x 768  
Elo 5 Wires Resistive Bezel Free Touch  
Intel® Bay Trail-D J1900 2.0G up to 2.4G, 2M Cache  
2G 204pin DDR3L-1333, SO-DIMM x 2 Max Support up to 8GB  
Internal 2.5" type SATA HDD x 1  
Windows 7, POS Ready7, Window 8.1, Industry Pro Retail 8.1, Linux (Ubuntu)

Options

3 tracks magnetic reader  
Customer display module (2 x 20 VFD), 2nd display  
Biometric Reader, Smart card Reader, I-Button, RFID reader

I/O Interface

4 \* COM ports [COM1~4 at back I/O (Powered with DC+5/+12V, COM1~2 by BIOS Selection; COM 3~4 by jumper setting )]  
1 \* DB-15 VGA port  
1 \* RJ11 port for 2 cash drawer (DC+24V)  
1 \* RJ-45 LAN port with activity and link LEDs  
1 \* PS/2 KB  
1 \* DC+12v out Jack  
6 \* USB (5 \* USB 2.0 + 1 \* USB 3.0)  
1 \* DC +12V input power-jack  
1 \* Mini PCI-e, Support Wireless LAN module

Expansion Options

Power Supply  
Storage Temperature  
Operating Temperature  
Operating Humidity  
Dimensions  
Certification

AC100~240v / DC+12V, 90 W power adaptor  
-20°C ~ 40°C  
0°C ~ 40°C  
15 % ~ 80 %  
Physical: 360mm (W) x 233mm (D) x 323mm (H)  
CE, FCC, VCCI, BSMI, Class A

Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong  
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | [www.eclinepos.com](http://www.eclinepos.com) | [sales@ecline.com.hk](mailto:sales@ecline.com.hk)

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P. 64310, Monterrey, N.L. México.  
+52 (81) 8370-5096 | 01 800 509-1818 | [www.eclinepos.com](http://www.eclinepos.com) | [ventas@ecline.com.mx](mailto:ventas@ecline.com.mx)